AMF

# **DOUGH TROUGH HOIST**





- Vertical or Slant Legs
- Ceiling or Free Standing Support Options
- Variety of Chute and Gate Options
- Custom Design for Special Applications



## **DOUGH TROUGH HOIST**

## **FEATURES & BENEFITS**

- The trough hoist is available in either vertical or slant leg type. The complete hoist is fabricated from heavy gauge steel plate. Lift chains are mounted inside the legs and driven by sprockets welded to the top main shaft and secured to the hoist legs via special heavy duty roller bearings.
- To ensure adequate static and shock load capacities, uses #120 chain having 34,000 pound tensile strength. This provides the hoist with a 20:1 safety factor.
- For added safety and simplicity, the gearbox is mounted directly onto the main shaft and is protected by a torque limiter, which will turn the motor off in case of overloading.
- To provide additional safety, the hoist is equipped with special safety latches that prevent the cradle and trough from falling in the unlikely event of chain breakage.
- The cradle is custom built to suit your specific trough requirements.
- Hoist is supplied with stationary chute. Chutes are designed and built to accommodate all types of mixers or dividers.
- New 3 HP Nord Gear drive unit (TEFC).
- All electrical wiring is NEMA 12 in waterproof conduits with Allen Bradley controls.
- Steel-it exterior finish.




Safety Latch Engaged

### OPTIONS


- Chute tilting kit
- Stainless steel legs 5' (1524 mm) or full length
- Stainless steel cradle in lieu of mild steel
- Free standing structure (mild or stainless steel)
- Water spray manifold

- Special cradle for two different heights of dough trough
- New SEW Eurodrive 3 HP (in lieu of Nord Gear)
- **Gate options**
- **Guillotine cutter option**

## **DIMENSIONAL DRAWING**



TROUGH HOIST-DIVIDER



TROUGH HOIST-MIXER

#### Headquarters:

2115 W. Laburnum Ave. Richmond, Virginia 23227 Tel: 1-800-225-3771 or 1-804-355-7961

Fax: 1-804-342-9724

**Europe Office:** West Park Ring Road Leeds LS16 6QQ England Tel: 44-1132-787110

Fax: 44-1132-741415 sales-europe@amfbakery.com

AMF's focus on continuous improvement may result in changes to machinery specifications without notice. Asia Office:

Room 801 A-Building Thunis Dev. Building No. 11 Hui Xin East St. Chaoyang District Beijing, China 100029 Tel: 86-10-64823613

Fax: 86-10-64934259 sales-asia@amfbakery.com FOR MORE INFORMATION PLEASE CALL YOUR ACCOUNT MANAGER OR

800-BAKERS-1

www.amfbakerv.com

08/2008